

AiO²—builds upon our original AiO with new features, while maintaining its core functions as a multipurpose audio interfacing tool. It has been redesigned to address up-to-date audio needs in the professional AV market.

As well as retaining the original AiO's features, this new and improved version has switchable VU metering of input or output signals, Headphone monitoring (with personal volume control), plus switchable 48V Phantom power for your condenser microphones.

Main Features

- Balanced audio Input and Output on industry standard XLR
- LED VU switchable monitoring of Input and Output
- USB powered
- Line or Mic level inputs
- Optional Phantom Power for Input when using powered condenser mics
- Ground lift switch on the output XLRs
- Independent variable input level control for Ch1 and Ch2

3 Year Limited Factory Warranty

Specifications:

Power

USB powered 250mA Max 5V
Switchable 48V Phantom Power

Signals

Balanced line level and/or headset (Desk PFL out)
Audio line 0dB out
Audio in 0dB and Mic -40dB
Bandwidth 20Hz - 20kHz

Control Switches

Stereo/Mono, GND Lift, Phantom Power, In/Out Monitor

Connections

USB A-B from host computer, Balanced XLR in and out

Note XLR cables are not included as standard.

Interspace Industries

Unit 7 Polaris Centre, 41 Brownfields, Welwyn Garden City, Hertfordshire, AL7 1AN, UK
call: +44 (0) 1462 600 101 email: moreinfo@interspaceind.com web: www.interspaceind.com

Disclaimer: Whilst all care is taken to ensure accuracy, Interspace Industries Ltd accepts no responsibility for any errors or omissions, whether implied or otherwise interpreted. All specifications subject to change without notice.



The Next Stage in Professional Audio Interfacing



Accessories

USB A-B cable supplied

Note: Do not use at high levels—Take care of your hearing!

