

ATBB¹

ATBB Analogue termination to unBal Box. This is the PCBB in reverse—balance line in to unbalanced out on 3.5mm jack.

This is for use on systems that have a mini jack input for stereo line or for stereo mic input.

The Ground will isolate the ground from the source for rejection of ground loop hum.

The Pad will pad the signal to about 36dB.

The Stereo/ Mono switch will join the output pairs via a resistive element to give both channels the same signal.

- ✓ Isolation of Hum
- ✓ Line to Mic Pad
- ✓ Gnd Lift
- ✓ Stereo input—to stereo \ mono output
- ✓ Passive
- ✓ Fixed output lead

3 Year Limited Factory Warranty

Specifications

Power

None

Signals

Balanced (XLR) Line level Audio in

Switchable Unbalanced line/mic level out (3.5mm Jack)

Dimensions mm (inch)

D x W x H

71 (2 8/10") x 64 (2 1/2") x 40 (1 6/10")

Captive lead length 1.8m (6ft)

Weight each

218g (8oz)

Note XLR cables and not included as standard.

Interspace Industries

Unit 1F Tewin Court, Tewin Road, Welwyn Garden City, Hertfordshire, AL7 1AU, UK

call: +44 (0) 1462 600 101 email: moreinfo@interspaceind.com web: www.interspaceind.com

Disclaimer: Whilst all care is taken to ensure accuracy, Interspace Industries Ltd accepts no responsibility for any errors or omissions, whether implied or otherwise interpreted. All specifications subject to change without notice.



Analogue Termination to unBal Box.



Accessories

