

# USB BalBox

**USB Balance Box** eliminates hum problems when connecting audio from your presentation computer source. Hum can happen anywhere, you don't have to be running your audio signal a long distance. Power supplies, fluorescent lights and all sorts of equipment can cause noise that is picked up by your audio input cables.

## Main Features

- True audio reproduction
- Improved Bandwidth
- 600ohm line level driven output
- Earth (Ground) lift
- Left/Right XLR output connectors are standard for live events audio
- USB powered
- Compact size

## 3 Year Limited Factory Warranty

### Specifications:

#### Signals:

Typical USB input  
Bandwidth: 100Hz to 18KHz signal levels

#### Control Switches:

Earth (Ground) lift  
Stereo to Mono

#### Connections:

USB input  
Output: 2male XLR

#### Dimensions mm (inch):

DxWxH: 71(2<sup>4</sup>/<sub>5</sub>)x 64(2<sup>1</sup>/<sub>2</sub>)x 40(1<sup>3</sup>/<sub>5</sub>)  
Supplied USB input cable

#### Weight:

218g / 8oz

#### Power:

USB powered

Interspace Industries

Unit 1A, 126 Great North Road, Hatfield, Hertfordshire, AL9 5JN

Call: +44 (0) 870 770 8088, Fax: +44 (0) 870 770 8089

Email: [moreinfo@interspaceind.com](mailto:moreinfo@interspaceind.com) web: [www.interspaceind.com](http://www.interspaceind.com)



*The USB 'Hum' Eliminator*

